

Plug 'n Play

Instant On/Instant Off™

EMP Monitor Software

3LCD

WXGA



Epson Projectors.
The #1 projector brand in the world.



The Number One Projector Brand In The World.



Combining best-in-class value with world-class performance, our business projector line-up delivers powerful image quality, incredible color, and the advanced features you need to enhance collaboration while ensuring a total low cost of ownership.

Long Lasting, Energy Efficient E-TORL™ Lamps:

Maximizes light using micro-reflectors. Saves on expenses without sacrificing light output or clarity of detail.

Lens Shift:

Provides installation flexibility. Vertical and horizontal shift makes installing around room obstacles easy.

Direct On/Power Off:

On/Off power of installed projectors controlled by simple outlet switch.

Quick-Connect Wireless and USB Key:

Makes projecting wirelessly from a PC easier than ever. Creates an ad-hoc connection to the projector from a PC.

Closed Captioning:

A built-in closed captioning decoder means convenience and savings. No additional hardware or software are required to project closed captioning on the big screen or in a conference room.

Native WXGA (1280x800) Resolution:

Ensures amazing detail and makes it easy to deliver images from your widescreen computer or HD video content — all with amazing clarity.

Easy One-Step Plug n' Play Capability:

Just connect the projector to a PC using a standard USB cable. Eliminates the need for bulky VGA cable or computer function keys to begin the presentation.

EasyMP®:

Easy monitoring and control. Check and control networked projector settings remotely, even via the web, with included software. Wired or wireless connectivity with advanced wireless security. Enables multi-screen display and other presentation features.

3LCD Technology:


3 chips in EVERY projector for full-time color. With its 3-chip design, 3LCD delivers clear and vibrant images, so true-to-life you may not believe your eyes.

Comprehensive Warranty with Convenient Road Service








Epson projector customers receive first-class service with Epson's standard 2-Year limited warranty, including next business day Road Service and a dedicated toll-free support line.*

For more information visit www.epson.com/projectors

*Replacement projectors typically shipped within 24 hours. Actual delivery time may vary.

Large Rooms and Auditoriums							
							
	PowerLite Pro G5350NL	PowerLite Pro G5200WNL	PowerLite Pro G5150NL	PowerLite G5000	PowerLite 6110i	PowerLite 1825	PowerLite 1810p
Basics							
Lumens - Color/White*	5000/5000	4200/4200	4000/4000	4000/4000	3500/3500	3500/3500	3500/3500
Native Resolution**	XGA	WXGA	XGA	XGA	XGA	XGA	XGA
Native Aspect Ratio***	4:3	16:10	4:3	4:3	4:3	4:3	4:3
Weight (lbs)	15.0 lb	14.81 lb	14.8 lb	14.55 lb	15.4 lb	6.9 lb	6.5 lb
Dimensions (inches)†	18.5 x 13.26 x 5.94	18.5 x 13.26 x 5.94	18.5 x 13.26 x 5.94	18.5 x 13.26 x 5.94	18.3 x 13.4 x 6.3	13.6 x 10.1 x 3.7	13.6 x 10.1 x 3.7
Contrast Ratio	1000:1	800:1	1000:1	1000:1	600:1	500:1	500:1
Zoom Lens (Ratio)†††	1.64-2.53‡	1.64-2.53‡	1.64-2.53‡	1.8x	1.6x	1.6x	1.6x
Lamp Life High/Eco (Hours)	2000/3000	2000/3000	2000/3000	2000/3000	3500/4000	2500/3000	2500/3000
Power Consumption							
Power On (Watts)	423W	423W	343W	343W	331W	306W	306W
Standby Network/Comm On	10W	10W	10W	10W	10.4W	12W	13W
Standby Network/Comm Off	0.4W	0.4W	0.4W	0.4W	0.4W	2.6W	2.6W
Efficiency (Watts/Lumen)††	0.08	0.10	0.09	0.09	0.09	0.09	0.09
Value-Added Features							
Built-in Speaker (Watts)	7W	7W	7W	–	5W	5W	5W
Closed Captioning	YES	YES	YES	YES	YES	YES	YES
A/V Mute Slide Door	–	–	–	–	–	YES	YES
Direct On/Direct Off	YES	YES	YES	YES	YES	YES	YES
Message Broadcasting†††	–	–	–	–	–	–	–
Plug 'n Play Features†††							
USB Mouse/Keyboard Control	YES	–	YES	–	–	YES	YES
USB Plug 'n Play Image/Video	YES	–	YES	–	–	YES	–
USB Plug 'n Play Audio	–	–	–	–	–	–	–
Other Connectivity Features							
PC-Free Presentations via USB A	YES	–	YES	–	–	YES	–
Quick-Connect Wireless via USB Key	Optional Accessory	–	Optional Accessory	–	–	Optional Accessory	–
LAN Networking & Control							
Monitor & Control	Wired	RJ-45 x 1 (100MB)	RJ-45 x 1 (100MB)	RJ-45 x 1 (100MB)	RJ-45 x 1 (100MB)	RJ-45 x 1 (100MB)	–
	Wireless††	Optional Module	–	Optional Module	–	–	Included
Networking plus Content Over IP	Wired	RJ-45 x 1 (100MB)	RJ-45 x 1 (100MB)	RJ-45 x 1 (100MB)	–	–	RJ-45 x 1 (100MB)
	Wireless††	Optional Module	–	Optional Module	–	–	Included
Easy MP Network Projection	YES	–	YES	–	–	YES	–
Windows Vista Network Projector Compatible	YES	–	YES	–	–	YES	–
Flexible Features for Easy Installations							
Quick-Corner® Adjustments	YES	YES	YES	YES	–	YES	YES
Lens Shift (Vertical & Horizontal)	YES	YES	YES	YES	–	–	–
Optional Bayonet Lenses‡	5	5	5	–	–	–	–
Other Interfaces							
Computer(VGA)/Component	Mini D-sub HD 15 pin x 2 5BNC Component x 1	Mini D-sub HD 15 pin x 2 5BNC Component x 1	Mini D-sub HD 15 pin x 2 5BNC Component x 1	Mini D-sub HD 15 pin x 2	Mini D-sub HD 15 pin x 2	Mini D-sub HD 15 pin x 2	Mini D-sub 15 pin x 2
S-Video	Mini DIN x 1	Mini DIN x 1	Mini DIN x 1	Mini DIN x 1	Mini DIN x 1	Mini DIN x 1	Mini DIN x 1
Composite Video	RCA x 1 BNC x 1	RCA x 1 BNC x 1	RCA x 1 BNC x 1	RCA x 1 BNC x 1	RCA x 1	RCA x 1	RCA x 1
Audio In	RCA (L & R) x 1 Mini Stereo x 1	RCA (L & R) x 1 Mini Stereo x 1	RCA (L & R) x 1 Mini Stereo x 1	RCA (L & R) x 1 Mini Stereo x 1	RCA (L & R) x 1 Mini Stereo x 3	RCA (L & R) x 1 Mini Stereo x 2	RCA x 2 (in Common with Analog RGB Audio Terminal)
Variable Audio Out	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
USB 2.0 Connectors	USB B x 1 USB A x 1	–	USB B x 1 USB A x 1	–	–	Type B x 1 Type A x 1	Type B x 1
HDMI	HDMI x 1	HDMI x 1	HDMI x 1	–	–	–	–
Monitor Out	Mini D-sub 15 pin x 1	Mini D-sub 15 pin x 1	Mini D-sub 15 pin x 1	–	Mini D-sub 15 pin x 1	Mini D-sub 15 pin x 1	Mini D-sub 15 pin x 1
Serial Control	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Other	Hardwire Remote Jack x 1 SD Card Slot	Hardwire Remote Jack x 1	Hardwire Remote Jack x 1 SD Card Slot	–	–	Hardwire Remote Jack x 1 Compact Flash x 1 (3.3v)	Hardwire Remote Jack x 1

Ultra Mobile/Small-Medium Rooms							
							
	PowerLite 1735W	PowerLite 1730W	PowerLite 1725	PowerLite 1720	PowerLite 1715c	PowerLite 410W	PowerLite 826W
Basics							
Lumens - Color/White*	3000/3000	3000/3000	3000/3000	3000/3000	2700/2700	2000/2000	2500/2500
Native Resolution**	WXGA	WXGA	XGA	XGA	XGA	WXGA	WXGA
Native Aspect Ratio***	16:10	16:10	4:3	4:3	4:3	16:10	16:10
Weight (lbs)	3.96 lb	3.74 lb	3.96 lb	3.74 lb	3.7 lb	7.9 lb	7.0 lb
Dimensions (inches)†	11.2 x 7.9 x 2.8	11.2 x 7.9 x 2.8	11.2 x 7.9 x 2.8	11.2 x 7.9 x 2.8	10.7 x 7.6 x 3.1	12.9 x 10.7 x 6.2	12.9 x 9.8 x 4.3
Contrast Ratio	Up to 2000:1	Up to 2000:1	Up to 2000:1	Up to 2000:1	400:1	500:1	Up to 2000:1
Zoom Lens (Ratio)†††	1.2x	1.2x	1.2x	1.2x	1.2x	1.35x	1.6x
Lamp Life High/Eco (Hours)	3000/4000	3000/4000	3000/4000	3000/4000	2000/3000	3000/4000	5000/6000
Power Consumption							
Power On (Watts)	243W	243W	243W	243W	244W	251W	290W
Standby Network/Comm On	9W	–	9W	–	18W	4.9W	6W
Standby Network/Comm Off	4W	4W	4W	4W	4W	4.2W	4.1W
Efficiency (Watts/Lumen)††	0.08	0.08	0.08	0.08	0.09	0.13	0.10
Value-Added Features							
Built-in Speaker (Watts)	1W	1W	1W	1W	1W	10W	10W
Closed Captioning	YES	YES	YES	YES	–	YES	YES
A/V Mute Slide Door	YES	YES	YES	YES	YES	–	YES
Direct On/Direct Off	YES	YES	YES	YES	–	YES	YES
Message Broadcasting††††	–	–	–	–	–	–	YES
Plug 'n Play Features†††							
USB Mouse/Keyboard Control	YES	YES	YES	YES	YES	–	YES
USB Plug 'n Play Image/Video	YES	–	YES	–	YES	–	YES
USB Plug 'n Play Audio	YES	–	YES	–	–	–	–
Other Connectivity Features							
PC-Free Presentations via USB A	YES	–	YES	–	YES	–	YES
Quick-Connect Wireless via USB Key	YES/Key Included	–	YES/Key Included	–	–	–	Optional Accessory
LAN Networking & Control							
Monitor & Control	Wired	Optional Module	–	Optional Module	–	Optional Module	RJ-45 x 1 (100MB)
	Wireless††	Included	–	Included	–	Included	Optional Module
Networking plus Content Over IP	Wired	Optional Module	–	Optional Module	–	Optional Module	RJ-45 x 1 (100MB)
	Wireless††	Included	–	Included	–	Included	Optional Module
Easy MP Network Projection	YES	–	YES	–	YES	–	YES
Windows Vista Network Projector Compatible	YES	–	YES	–	–	–	–
Flexible Features for Easy Installations							
Quick-Corner® Adjustments	–	–	–	–	–	–	–
Lens Shift (Vertical & Horizontal)	–	–	–	–	–	–	–
Optional Bayonet Lenses†	–	–	–	–	–	–	–
Other Interfaces							
Computer(VGA)/Component	Mini D-sub HD 15 pin x 1	Mini D-sub HD 15 pin x 1	Mini D-sub HD 15 pin x 1	Mini D-sub HD 15 pin x 1	Mini D-sub HD 15 pin x 1	Mini D-sub HD 15 pin x 2	Mini D-sub HD 15 pin x 2
S-Video	Mini DIN x 1	Mini DIN x 1	Mini DIN x 1	Mini DIN x 1	Mini DIN x 1	Mini DIN x 1	Mini DIN x 1
Composite Video	RCA x 1	RCA x 1	RCA x 1	RCA x 1	RCA x 1	RCA x 1	RCA x 1
Audio In	Mini Stereo x 1 in or out	Mini Stereo x 1 in or out	Mini Stereo x 1 in or out	Mini Stereo x 1 in or out	Mini Stereo x 1 in or out	RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2
Variable Audio Out	Mini Stereo x 1 in or out	Mini Stereo x 1 in or out	Mini Stereo x 1 in or out	Mini Stereo x 1 in or out	Mini Stereo x 1 in or out	Mini Stereo x 1	Mini Stereo x 1
USB 2.0 Connectors	Type B x 1 Type A x 1	Type B x 1	Type B x 1 Type A x 1	Type B x 1	Type B x 1 Type A x 1	–	USB B x 1 USB A x 1
HDMI	–	–	–	–	–	–	–
Monitor Out	–	–	–	–	–	Mini D-sub 15 pin x 1	Mini D-sub 15 pin x 1
Serial Control	–	–	–	–	–	RS-232c x 1	RS-232c x 1
Other	–	–	–	–	–	–	Microphone Stereo Mini Jack

Small-Medium Rooms							
							
	PowerLite 825	PowerLite 85	PowerLite 84	PowerLite 83+	PowerLite W6	PowerLite 78	PowerLite S6
Basics							
Lumens - Color/White*	3000/3000	2600/2600	2600/2600	2200/2200	2000/2000	2200/2200	2200/2200
Native Resolution**	XGA	XGA	XGA	XGA	WXGA	XGA	SVGA
Native Aspect Ratio***	4:3	4:3	4:3	4:3	16:10	4:3	4:3
Weight (lbs)	7.0 lb	7.0 lb	6.9 lb	6.4 lb	6.2 lb	6.2 lb	6.0 lb
Dimensions (inches)†	12.9 x 9.8 x 4.3	12.9 x 9.8 x 4.3	12.9 x 9.8 x 4.3	12.9 x 9.6 x 3.6	12.9 x 9.6 x 3.6	12.9 x 9.6 x 3.6	12.9 x 9.6 x 3.6
Contrast Ratio	Up to 2000:1	Up to 2000:1	Up to 2000:1	400:1	Up to 2000:1	Up to 2000:1	Up to 2000:1
Zoom Lens (Ratio)†††	1.6x	1.6x	1.6x	1.2x	1.2x	1.2x	1.35x
Lamp Life High/Eco (Hours)	5000/6000	5000/6000	5000/6000	3000/4000	3000/4000	3000/4000	3000/4000
Power Consumption							
Power On (Watts)	289W	289W	289W	248W	246W	260W	246W
Standby Network/Comm On	7.9W	7.9W	7.9W	5W	–	–	–
Standby Network/Comm Off	1.9W	1.9W	1.9W	4.1W	3W	5W	4W
Efficiency (Watts/Lumen)††	0.10	0.13	0.13	0.11	0.12	0.12	0.11
Value-Added Features							
Built-in Speaker (Watts)	10W	10W	10W	10W	7W	1W	1W
Closed Captioning	YES	YES	YES	YES	–	–	–
A/V Mute Slide Door	YES	YES	YES	YES	YES	YES	YES
Direct On/Off	YES	YES	YES	YES	–	–	–
Message Broadcasting††††	YES	YES	–	–	–	–	–
Plug 'n Play Features†††							
USB Mouse/Keyboard Control	YES	YES	YES	–	YES	YES	YES
USB Plug 'n Play Image/Video	YES	YES	YES	–	YES	YES	YES
USB Plug 'n Play Audio	–	–	–	–	–	–	–
Other Connectivity Features							
PC-Free Presentations via USB A	YES	YES	–	–	YES	–	–
Quick-Connect Wireless via USB Key	Optional Accessory	Optional Accessory	–	–	–	–	–
LAN Networking & Control							
Monitor & Control	Wired	RJ-45 x 1 (100MB)	RJ-45 x 1 (100MB)	RJ-45 x 1 (100MB)	RJ-45 x 1 (100MB)	–	–
	Wireless††	Optional Module	Optional Module	–	–	–	–
Networking plus Content Over IP	Wired	RJ-45 x 1 (100MB)	RJ-45 x 1 (100MB)	–	–	–	–
	Wireless††	Optional Module	Optional Module	–	–	–	–
Easy MP Network Projection	YES	YES	–	–	–	–	–
Windows Vista Network Projector Compatible	–	–	–	–	–	–	–
Flexible Features for Easy Installations							
Quick-Corner® Adjustments	–	–	–	–	–	–	–
Lens Shift (Vertical & Horizontal)	–	–	–	–	–	–	–
Optional Bayonet Lenses‡	–	–	–	–	–	–	–
Other Interfaces							
Computer(VGA)/Component	Mini D-sub HD 15 pin x 2	Mini D-sub HD 15 pin x 2	Mini D-sub HD 15 pin x 2	Mini D-sub HD 15 pin x 2	Mini D-sub HD 15 pin x 1	Mini D-sub HD 15 pin x 1	Mini D-sub HD 15 pin x 1
S-Video	Mini DIN x 1	Mini DIN x 1	Mini DIN x 1	Mini DIN x 1	Mini DIN x 1	Mini DIN x 1	Mini DIN x 1
Composite Video	RCA x 1	RCA x 1	RCA x 1	RCA x 1	RCA x 1	RCA x 1	RCA x 1
Audio In	RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1	RCA (L & R) x 1	RCA (L & R) x 1
Variable Audio Out	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	–	–	–
USB 2.0 Connectors	USB B x 1 USB A x 1	USB B x 1 USB A x 1	Type B x 1	–	Type B x 1	Type B x 1 Type A x 1	Type B x 1
HDMI	–	–	–	–	YES	–	–
Monitor Out	Mini D-sub 15 pin x 1	Mini D-sub 15 pin x 1	Mini D-sub 15 pin x 1	Mini D-sub 15 pin x 1	–	Mini D-sub 15 pin x 1	–
Serial Control	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	–	–	–
Other	Microphone Stereo Mini Jack	Microphone Stereo Mini Jack	Microphone Stereo Mini Jack	–	SD Card Slot	–	–

* Light output varies depending on modes (color light output and white light output). White light output measured using ISO 21118. **WXGA (1280 x 800), XGA (1024 x 768), SVGA (800x600). ***Native 16:10 supports 16:9 and 4:3, and Native 4:3 supports 16:9. † Dimensions including feet and standard lens. †† In High Brightness mode. ††† Plug 'n Play is Mac compatible via DVI to VGA adapter (not included). ‡ Zoom ratio varies depending on lens selected.

‡‡ All wireless is 802.11 a/b/g. ‡‡‡ 410W and S6 are digital zoom. All others are optical zoom. ‡‡‡‡ Plug-in available at www.epson.com



EPSON®
EXCEED YOUR VISION

Epson America, Inc. • 3840 Kilroy Airport Way • Long Beach, CA 90806 • www.Epson.com/projectors

CPD-VM22835